

01GT SYNTH IQ FORMULA 0W20

Description	<p>A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:</p> <ul style="list-style-type: none">- a lower fuel consumption- a high and very stable viscosity index- a high resistance against shearing- a fast cold start- a very strong resistance against oxidation- a safe lubrication film at very high temperatures- a very good detergency and dispersion- a very strong protection against wear, corrosion and foaming																		
Application	<p>A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1 Ö Gen 2.</p>																		
Specifications	<p>API SP Resource Conserving ILSAC GF-6A Meets the requirements of: GM dexos1 (TM) Gen 2 Chrysler MS 6395 Ford WSS-M2C947-A/B1 / WSS-M2C962-A1</p>																		
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,843</td></tr><tr><td>Viscosity -35 °C, mPa.s</td><td>4940</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>44,00</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>8,60</td></tr><tr><td>Viscosity Index</td><td>178</td></tr><tr><td>Flash Point COC, °C</td><td>222</td></tr><tr><td>Pour Point, °C</td><td>-36</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>8,5</td></tr><tr><td>Sulphate Ash, %</td><td>0,89</td></tr></table>	Density at 15 °C, kg/l	0,843	Viscosity -35 °C, mPa.s	4940	Viscosity 40 °C, mm ² /s	44,00	Viscosity 100 °C, mm ² /s	8,60	Viscosity Index	178	Flash Point COC, °C	222	Pour Point, °C	-36	Total Base Number, mgKOH/g	8,5	Sulphate Ash, %	0,89
Density at 15 °C, kg/l	0,843																		
Viscosity -35 °C, mPa.s	4940																		
Viscosity 40 °C, mm ² /s	44,00																		
Viscosity 100 °C, mm ² /s	8,60																		
Viscosity Index	178																		
Flash Point COC, °C	222																		
Pour Point, °C	-36																		
Total Base Number, mgKOH/g	8,5																		
Sulphate Ash, %	0,89																		