

01GT SYNTH IQ FORMULA 5W50

Description	 A nowadays universal full-synthetic motor oil, produced with synthetic base oils and a well balanced choice of advanced additives to obtain the following properties: a high and very stable viscosity index a high resistance against shearing a fast cold start a safe lubrication film at very high temperatures a very good detergency and dispersion a very strong protection against wear, corrosion and foaming 	
Application	This universal synthetic motor oil, recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below.	
Performance Level	Performance level ACEA A3/B4 API SN/CF MB 229.3 Porsche A40 VW 502.00/505.00	
Typicals	Density at 15 °C, kg/l Viscosity -30 °C, mPa.s Viscosity 40 °C, mm²/s Viscosity 100 °C, mm²/s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g Sulphate Ash, %	0,854 5940 114,30 17,90 174 236 -39 10,3 1,33

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website..