



## 01GT SYNTH IQ FORMULA 5W30

<b>Description</b>	<p>A fuel economy, universal, synthetic motor oil, developed according the most recent technology, based on specially selected synthetic base oils. By applying advanced additives the exceptional performance of this low SAPS motor oil is accentuated:</p> <ul style="list-style-type: none"> <li>- a lower fuel consumption</li> <li>- suitable for modern catalysts</li> <li>- low combustion ash building (low SAPS)</li> <li>- a fast cold start</li> <li>- a safe lubrication film at high temperatures</li> <li>- a very good detergency and dispersion</li> <li>- a very strong protection against wear, corrosion and foaming</li> </ul>	
<b>Application</b>	<p>A universal, synthetic, fuel economy, specially composed motor oil, recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its special composition this product can be applied in vehicles with modern three way catalysts and diesel particle filters. Due to its low SAPS content this motor oil contributes to the extension of the lifetime of particle filters for diesel engines.</p> <p><b>Warning:</b> <i>These oils have the lowest SAPS limits and may be unsuitable for use in some engines.</i></p>	
<b>Performance Level</b>	<p>ACEA C1 Meets the requirements of Jaguar Land Rover STJLR.03.5005</p>	
<b>Typicals</b>	<p>Density at 15 °C, kg/l Viscosity -30 °C, mPa.s Viscosity 40 °C, mm<sup>2</sup>/s Viscosity 100 °C, mm<sup>2</sup>/s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g Sulphate Ash, %</p>	<p>0,847 3900 52,50 9,46 166 224 -39 6,6 0,45</p>