

01GT SYNTH IQ FORMULA 5W30

Description	LB Extendo NF 5W30 is a product of the LB (Level Back-up) product range. These products are based on the officially approved formulas, using the same high-quality additives, but the base oils have been replaced with equivalent alternatives. This creates equivalent products in terms of quality, with a performance level corresponding to the originally approved products. However, because no field tests have been conducted, the product may be claimed only to meet the mentioned performance levels.	
Application	This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.	
Specifications	Performance level: ACEA C3 API SP BMW Longlife-04 MB 229.31/229.51/229.52 Opel OV0401547 Porsche C30 VW 504.00/507.00	
Typicals	Density at 15 °C, kg/l	0,853
	Viscosity -30 °C, mPa.s	5050
	Viscosity 40 °C, mm ² /s	68,80
	Viscosity 100 °C, mm ² /s	12,20
	Viscosity Index	179
	Flash Point COC, °C	220
	Pour Point, °C	-42
	Total Base Number, mgKOH/g	8,3
	Sulphate Ash, %	0,75