



01GT SYNTH IQ FORMULA 5W40

Description	LB Specialsynth NF 5W40 is a product of the LB (Level Back-up) product range. These products are based on the officially approved formulas, using the same high-quality additives, but the base oils have been replaced with equivalent alternatives. This creates equivalent products in terms of quality, with a performance level corresponding to the originally approved products. However, because no field tests have been conducted, the product may be claimed only to meet the mentioned performance levels.	
Application	This universal synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.	
Performance Level	Performance level ACEA C3 API SN/CF BMW Longlife-04 GM dexos 2 MB 229.51 Porsche A40 VW 505.00/505.01	
Typicals	Density at 15 °C, kg/l	0,849
	Viscosity -30 °C, mPa.s	6320
	Viscosity 40 °C, mm ² /s	78,80
	Viscosity 100 °C, mm ² /s	13,40
	Viscosity Index	174
	Flash Point COC, °C	230
	Pour Point, °C	-39
	Total Base Number, mgKOH/g	7,4
	Sulphate Ash, %	0,78