



## 01GT SYNTH IQ FORMULA 0W30

<b>Description</b>	<p>A modern, synthetic, fuel economy, universal motor oil based on special selected synthetic base oils, amongst others esters, with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:</p> <ul style="list-style-type: none"> <li>- a lower fuel consumption</li> <li>- a high and very stable viscosity index</li> <li>- a high resistance against shearing</li> <li>- a very fast cold start</li> <li>- a very strong resistance against oxidation</li> <li>- a safe lubrication film at very high temperatures</li> <li>- a very good detergency and dispersion</li> <li>- a very strong protection against wear, corrosion and foaming</li> </ul>	
<b>Application</b>	<p>A universal, ester fortified, fuel economy, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.</p>	
<b>Performance Level</b>	<p>Performance level            ACEA A3/B4            API SH/CF            BMW Longlife-01            MB 229.3/226.5            Renault RN0700            VW 502.00/505.00            API SN/CF *)            *) API SN quality only; not-licensable due to phosphorus-limit</p>	
<b>Typicals</b>	<p>Density at 15 °C, kg/l            Viscosity -35 °C, mPa.s            Viscosity 40 °C, mm<sup>2</sup>/s            Viscosity 100 °C, mm<sup>2</sup>/s            Viscosity Index            Flash Point COC, °C            Pour Point, °C            Total Base Number, mgKOH/g            Sulphate Ash, %</p>	<p>0,849            5930            55,80            10,10            171            230            -45            10,3            1,33</p>