



01GT SYNTH IQ FORMULA 5W40

Description A very modern, synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

Performance Level ACEA A3/B4
API SN/CF
MB-Approval 229.3/229.5
Meets the requirements of
BMW Longlife-01
VW 502.00/505.00/501.01
Porsche A40
Renault RN0700/RN0710
Opel GM-LL-B-025
PSA B71 2296

Typicals	Density at 15 °C, kg/l	0,856
	Viscosity -30 °C, mPa.s	6320
	Viscosity 40 °C, mm ² /s	86,30
	Viscosity 100 °C, mm ² /s	14,00
	Viscosity Index	167
	Flash Point COC, °C	218
	Pour Point, °C	-45
	Total Base Number, mgKOH/g	10,1
	Sulphate Ash, %	1,09