

01GT SYNTH IQ FORMULA 5W30

Description

A modern, synthetic, universal motor oil based on special selected synthetic base oils, amongst others esters, with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This universal, ester fortified, fuel saving synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.

Performance Level

Performance level

ACEA C3 API SN

BMW Longlife-04 GM dexos 2

MB 229.51/229.52 VW 505.00/505.01

Typicals

Density at 15 °C, kg/l	0,847
Viscosity -30 °C, mPa.s	3750
Viscosity 40 °C, mm²/s	56,80
Viscosity 100 °C, mm²/s	11,00
Viscosity Index	190
Flash Point COC, °C	218
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,2
Sulphate Ash, %	0,78