



## LKW MAX POWER & TORQUE FLEET LINE LSP 15W40

<b>Description</b>	<p>A universal multigrade engine oil produced with special selected solvent refined base oils and additives. This engine oil has the following properties:</p> <ul style="list-style-type: none"> <li>- a very good detergency prevents deposits in the engine</li> <li>- a very good dispersion that prevents from precipitation and sludge</li> <li>- a powerful action against wear, corrosion and foam</li> <li>- a stable viscosity index</li> <li>- suitable for extended drain intervals</li> <li>- low ash contents</li> </ul>	
<b>Application</b>	<p>This universal lubricating oil is suitable for gasoline or diesel engines, with or without super-charging. This motor oil is suitable for application in mixed fleets.</p>	
<b>Performance Level</b>	<p>ACEA E7            API CH-4/SJ            Meets the requirements of            MAN M 3275-1            MB 228.1            Cat ECF-1-a            Cummins CES 20076/20077            Deutz DQC III-10            MTU Type 2</p>	
<b>Typicals</b>	<p>Density at 15 °C, kg/l            Viscosity -20 °C, mPa.s            Viscosity 40 °C, mm<sup>2</sup>/s            Viscosity 100 °C, mm<sup>2</sup>/s            Viscosity Index            Flash Point COC, °C            Pour Point, °C            Total Base Number, mgKOH/g            Sulphate Ash, %</p>	<p>0,872            5700            106,40            14,50            140            216            -33            11,1            1,43</p>