



LKW MAX POWER & TORQUE FLEETFORCE CI-4 15W50

Description

This modern, universal applicable engine oil is produced with high quality solvent refined base oils and a well-balanced choice of additives. This multigrade engine oil has the following properties:

- a very good detergency prevents deposits in the engine
- a very good dispersion that prevents from precipitation and sludge
- a powerful action against corrosion and foam
- a high and stable viscosity index
- a low sulphated ash content
- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners

Application

This universal engine oil is suitable for the lubrication of gasoline and diesel engines, with or without turbo-loading, under heavy operating conditions and all the year round. This oil is excellent suitable for mixed fleets and can be applied in e.g. Euro 4 and Euro 5 engines. Due to its special composition longer drain intervals are possible with this motor oil.

Performance Level

Performance level
ACEA A3/B4, E7
API CI-4/SL
MB 228.3

Typicals

Density at 15 °C, kg/l	0,867
Viscosity -20 °C, mPa.s	6000
Viscosity 40 °C, mm ² /s	134,00
Viscosity 100 °C, mm ² /s	17,50
Viscosity Index	144
Flash Point COC, °C	215
Pour Point, °C	-36
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,45