



LKW MAX POWER & TORQUE ULTRA 15W40

Description	<p>LB Unifleet Ultra is a product of the LB (Level Back-up) product range. These products are based on the officially approved formulas, using the same high-quality additives, but the base oils have been replaced with equivalent alternatives. This creates equivalent products in terms of quality, with a performance level corresponding to the originally approved products. However, because no field tests have been conducted, the product may be claimed only to meet the mentioned performance levels.</p>	
Application	<p>This engine lubricant is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This product is suitable for application in Euro 4 and Euro 5 engines.</p>	
Performance Level	<p>Performance level ACEA E7 API CI-4/SL Cat ECF-1-a/ECF-2 Cummins CES 20077/20078 Detroit Diesel 93K215 Deutz DQC III-10 Global DHD-1 JASO DH-1 Mack EO-N/EO-M Plus MAN M 3275-1 MB 228.3 MTU Type 2 Renault VI RLD-2 Volvo VDS-3</p>	
Typicals	<p>Density at 15 °C, kg/l Viscosity -20 °C, mPa.s Viscosity 40 °C, mm²/s Viscosity 100 °C, mm²/s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g Sulphate Ash, %</p>	<p>0,878 5180 98,00 13,60 134 212 -36 11,1 1,43</p>