



## LKW MAX POWER & TORQUE LSP +PLUS 5W30

<b>Description</b>	LB Turbosynth LSP Plus 5W30 is a product of the LB (Level Back-up) product range. These products are based on the officially approved formulas, using the same high-quality additives, but the base oils have been replaced with equivalent alternatives. This creates equivalent products in terms of quality, with a performance level corresponding to the originally approved products. However, because no field tests have been conducted, the product may be claimed only to meet the mentioned performance levels.	
<b>Application</b>	This fuel saving lubricant has mainly been developed for heavy diesel engines even under the toughest operation conditions and all the year round. This product is very suitable for Euro 5 and Euro 6 engines in combination with diesel fuel with a low sulphur content. This engine oil is also suitable for application in engines with or without particle filters and exhaust catalyts. This motoroil is one of the group "low SAPS" lubricants.	
<b>Performance Level</b>	Performance level ACEA E6, E7, E9 API CJ-4/SN Cat ECF-3 Cummins CES 20081 Detroit Diesel 93K218 Deutz DQC IV-10 LA JASO DH-2 Mack EO-O PP/EO-N PP/EO-M Plus MAN M 3677/M 3477/M 3271-1 MB 228.31/228.51 MTU Type 3.1 Renault VI RLD-3 Scania Low Ash/LDF-4 Voith Class B Volvo VDS-4/VDS-3	
<b>Typicals</b>	Density at 15 °C, kg/l Viscosity -30 °C, mPa.s Viscosity 40 °C, mm <sup>2</sup> /s Viscosity 100 °C, mm <sup>2</sup> /s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g Sulphate Ash, %	0,855 6250 68,40 11,50 163 216 -39 9,3 0,99