



## Two Stroke HS (Low Smoke)

<b>Description</b>	<p>A two stroke engine oil formulated with carefully selected high quality mineral and synthetic base oils and special two stroke additives to achieve the following properties:</p> <ul style="list-style-type: none"> <li>- a perfect lubrication of all motor parts</li> <li>- an active detergency, preventing from deposits in the combustion zone and at the scavenger ports</li> <li>- preventing spark plugs from fouling, in this way securing an optimal output of the engine</li> <li>- a very effective activity against wear and corrosion</li> <li>- a very limited formation of smoke</li> <li>- selfmixing</li> </ul>	
<b>Application</b>	<p>This two stroke engine oil is advised for the lubrication of high speed aircooled two stroke engines under heavy duty load. This selfmixing two stroke engine oil may also be used for water cooled two stroke engines (radiator type cooling systems).</p>	
<b>Specifications</b>	<p>Performance level            API TC            JASO FD            Global GD            Husqvarna 272            ISO-L-EGD            2-Stroke DFI</p>	
<b>Typicals</b>	<p>Density at 15 °C, kg/l            Viscosity 40 °C, mm<sup>2</sup>/s            Viscosity 100 °C, mm<sup>2</sup>/s            Viscosity Index            Flash Point COC, °C            Pour Point, °C            Total Base Number, mgKOH/g            Sulphate Ash, %</p>	<p>0,870            64,60            9,50            129            116            -24            1,4            0,14</p>