



## ATF 9G

<b>Description</b>	<p>A very high graded, extremely low-viscosity automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:</p> <ul style="list-style-type: none"> <li>- excellent contribution to fuel economy</li> <li>- excellent lubrication</li> <li>- very good resistance against oxidation</li> <li>- very good thermal stability</li> <li>- excellent and very stable friction characteristics</li> <li>- excellent resistance against corrosion and foaming</li> <li>- excellent protection against wear</li> <li>- a very high and stable viscosity index</li> </ul>	
<b>Application</b>	<p>This premium synthetic product is specially formulated for the lubrication of certain Mercedes-Benz automatic transmissions with 9 gears. This oil contributes significantly to realizing fuel saving and can be used in automatic transmissions where an oil with the specification MB 236.17 is prescribed.</p>	
<b>Specifications</b>	<p>Performance level MB 236.17</p>	
<b>Typicals</b>	Density at 15 °C, kg/l	0,835
	Viscosity 40 °C, mm <sup>2</sup> /s	17,10
	Viscosity 100 °C, mm <sup>2</sup> /s	4,23
	Viscosity Index	161
	Flash Point COC, °C	174
	Pour Point, °C	-57