



ATF LongLife

Description	<p>A synthetic automatic transmission fluid, based on synthetic base oils, formulated with special friction modifiers to obtain the following properties:</p> <ul style="list-style-type: none"> - a very high and stable viscosity index - a very low pour point - an excellent stability against oxidation - a positive activity against wear, corrosion and foam - specific friction properties and consequently low noise and smooth switching - compatible with synthetic seals - a quick oil provision at cold start conditions - without dye 	
Application	<p>This fluid may be used for automatic transmissions of passenger cars and commercial vehicles. It is recommended to follow the instructions of the manufacturer.</p>	
Specifications	<p>Performance level Allison C4/TES-389 Cat TO-2 Ford Mercon/M2C138-CJ/166-H GM Dexron IID/IIIE/IIIF/IIIG/IIIH MAN 339 Typ Z1/V1/Typ Z2/V2 MB 236.1/236.5/236.6/236.7/236.9/236.10 Voith 55.6335/55.6336 Volvo 97340/97341 ZF TE-ML 02F/03D/04D/09/11A/11B/14A/14B/16L/17C</p>	
Typicals	<p>Density at 15 °C, kg/l Viscosity 40 °C, mm²/s Viscosity 100 °C, mm²/s Viscosity Index Flash Point COC, °C Pour Point, °C</p>	<p>0,843 35,50 7,63 192 214 -48</p>