

01GT SYNTH IQ FORMULA 0W30

Description	<p>This modern synthetic fuel economy motor oil is produced with special selected synthetic base oils and a well-balanced choice of advanced additives to obtain the following properties:</p> <ul style="list-style-type: none">- a lower fuel consumption- a high and stable viscosity index- a high resistance against shearing- a very fast cold start- a very strong resistance against oxidation- a safe lubrication film at high temperatures- a very good detergency and dispersion power- a very strong protection against wear, corrosion and foaming.																		
Application	<p>This fuel economy motor oil is recommended for use in petrol engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below.</p>																		
Specifications	API SP																		
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,844</td></tr><tr><td>Viscosity -35 °C, mPa.s</td><td>5200</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>54,30</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>10,00</td></tr><tr><td>Viscosity Index</td><td>174</td></tr><tr><td>Flash Point COC, °C</td><td>220</td></tr><tr><td>Pour Point, °C</td><td>-42</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>8,5</td></tr><tr><td>Sulphate Ash, %</td><td>0,89</td></tr></table>	Density at 15 °C, kg/l	0,844	Viscosity -35 °C, mPa.s	5200	Viscosity 40 °C, mm ² /s	54,30	Viscosity 100 °C, mm ² /s	10,00	Viscosity Index	174	Flash Point COC, °C	220	Pour Point, °C	-42	Total Base Number, mgKOH/g	8,5	Sulphate Ash, %	0,89
Density at 15 °C, kg/l	0,844																		
Viscosity -35 °C, mPa.s	5200																		
Viscosity 40 °C, mm ² /s	54,30																		
Viscosity 100 °C, mm ² /s	10,00																		
Viscosity Index	174																		
Flash Point COC, °C	220																		
Pour Point, °C	-42																		
Total Base Number, mgKOH/g	8,5																		
Sulphate Ash, %	0,89																		