

## 01GT SYNTH IQ FORMULA 0W20

<b>Description</b>	<p>A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:</p> <ul style="list-style-type: none"><li>- a lower fuel consumption</li><li>- a high and very stable viscosity index</li><li>- a high resistance against shearing</li><li>- a very fast cold start</li><li>- a very strong resistance against oxidation</li><li>- a safe lubrication film at very high temperatures</li><li>- a very good detergency and dispersion</li><li>- a very strong protection against wear, corrosion and foaming.</li></ul>	
<b>Application</b>	<p>A modern fuel economy, special composed synthetic motor oil suitable for use in petrol and diesel engines of passenger cars and delivery vans. Specially developed for use with the specified specifications.</p>	
<b>Specifications</b>	<p>ACEA C5 API SP Resource Conserving ILSAC GF-6A Meets the requirements of: Ford WSS-M2C947-B1 / WSS-M2C962-A1 Jaguar Land Rover STJLR.03.5006 MB 229.71/229.72 Opel OV0401547 Volvo VCC RBS0-2AE Chrysler MS-12145 Fiat 9.55535-GSX</p>	
<b>Typicals</b>	<p>Density at 15 °C, kg/l</p> <p>Viscosity -35 °C, mPa.s</p> <p>Viscosity 40 °C, mm<sup>2</sup>/s</p> <p>Viscosity 100 °C, mm<sup>2</sup>/s</p> <p>Viscosity Index</p> <p>Flash Point COC, °C</p> <p>Pour Point, °C</p> <p>Total Base Number, mgKOH/g</p> <p>Sulphate Ash, %</p>	<p>0,848</p> <p>6000</p> <p>42,60</p> <p>8,61</p> <p>186</p> <p>224</p> <p>-45</p> <p>7,5</p> <p>0,61</p>