

Specialsynth S 10W40

Description	<p>A universal engine oil, developed according to the latest techniques, based on specially selected high-quality and synthetic base oils, to which advanced additives have been added to obtain the following properties:</p> <ul style="list-style-type: none">- a high and stable viscosity index- a good resistance against shearing- a very fast cold start, even at very low temperatures- a safe lubrication film at very high temperatures- a very good detergency and dispersion power- a very strong protection against wear, corrosion and foaming.																
Application	<p>This universal engine oil is suitable for both newer and older petrol engines of (hybrid) passenger cars, mainly from Asian and North American brands, which are equipped with the latest technologies.</p>																
Specifications	<p>Performance level: API SP</p>																
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,859</td></tr><tr><td>Viscosity -25 °C, mPa.s</td><td>4990</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>93,40</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>14,20</td></tr><tr><td>Viscosity Index</td><td>157</td></tr><tr><td>Flash Point COC, °C</td><td>226</td></tr><tr><td>Pour Point, °C</td><td>-39</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>7,2</td></tr></table>	Density at 15 °C, kg/l	0,859	Viscosity -25 °C, mPa.s	4990	Viscosity 40 °C, mm ² /s	93,40	Viscosity 100 °C, mm ² /s	14,20	Viscosity Index	157	Flash Point COC, °C	226	Pour Point, °C	-39	Total Base Number, mgKOH/g	7,2
Density at 15 °C, kg/l	0,859																
Viscosity -25 °C, mPa.s	4990																
Viscosity 40 °C, mm ² /s	93,40																
Viscosity 100 °C, mm ² /s	14,20																
Viscosity Index	157																
Flash Point COC, °C	226																
Pour Point, °C	-39																
Total Base Number, mgKOH/g	7,2																