

GT Synth Pro Energy 10W40

Description	<p>This universal motor oil is based on high quality solvent refined mineral and synthetic base oils. Additives have been added to this to obtain the following properties:</p> <ul style="list-style-type: none">- a stable viscosity index- a fast cold start- a strong resistance against oxidation- a safe lubrication film at high temperature- a good detergency and dispersion- a strong protection against wear, corrosion and foaming.																		
Application	<p>A universal motor oil, recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.</p>																		
Specifications	<p>Performance level API SN/CF ACEA A3/B4 BMW Longlife-98 MB 229.1 VW 501.01/505.00</p>																		
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,871</td></tr><tr><td>Viscosity -25 °C, mPa.s</td><td>6570</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>90,60</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>13,60</td></tr><tr><td>Viscosity Index</td><td>152</td></tr><tr><td>Flash Point COC, °C</td><td>234</td></tr><tr><td>Pour Point, °C</td><td>-36</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>10,1</td></tr><tr><td>Sulphate Ash, %</td><td>1,29</td></tr></table>	Density at 15 °C, kg/l	0,871	Viscosity -25 °C, mPa.s	6570	Viscosity 40 °C, mm ² /s	90,60	Viscosity 100 °C, mm ² /s	13,60	Viscosity Index	152	Flash Point COC, °C	234	Pour Point, °C	-36	Total Base Number, mgKOH/g	10,1	Sulphate Ash, %	1,29
Density at 15 °C, kg/l	0,871																		
Viscosity -25 °C, mPa.s	6570																		
Viscosity 40 °C, mm ² /s	90,60																		
Viscosity 100 °C, mm ² /s	13,60																		
Viscosity Index	152																		
Flash Point COC, °C	234																		
Pour Point, °C	-36																		
Total Base Number, mgKOH/g	10,1																		
Sulphate Ash, %	1,29																		