

GT Synth Pro Energy 5W40

Description	<p>A synthetic universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which special additives are added to obtain the following properties:</p> <ul style="list-style-type: none">- a fast cold start- a safe lubrication film at high temperatures- a very good detergency and dispersion- a very strong protection against wear, corrosion and foaming																		
Application	<p>This synthetic universal "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its low SAPS content this product can be applied in vehicles with modern three way catalyts and diesel particle filters.</p>																		
Specifications	<p>Performance level: ACEA C3 API SN BMW Longlife-04 MB 229.51 VW 505.01</p>																		
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,847</td></tr><tr><td>Viscosity -30 °C, mPa.s</td><td>5160</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>81,90</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>13,80</td></tr><tr><td>Viscosity Index</td><td>174</td></tr><tr><td>Flash Point COC, °C</td><td>236</td></tr><tr><td>Pour Point, °C</td><td>-30</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>7,8</td></tr><tr><td>Sulphate Ash, %</td><td>0,77</td></tr></table>	Density at 15 °C, kg/l	0,847	Viscosity -30 °C, mPa.s	5160	Viscosity 40 °C, mm ² /s	81,90	Viscosity 100 °C, mm ² /s	13,80	Viscosity Index	174	Flash Point COC, °C	236	Pour Point, °C	-30	Total Base Number, mgKOH/g	7,8	Sulphate Ash, %	0,77
Density at 15 °C, kg/l	0,847																		
Viscosity -30 °C, mPa.s	5160																		
Viscosity 40 °C, mm ² /s	81,90																		
Viscosity 100 °C, mm ² /s	13,80																		
Viscosity Index	174																		
Flash Point COC, °C	236																		
Pour Point, °C	-30																		
Total Base Number, mgKOH/g	7,8																		
Sulphate Ash, %	0,77																		