

## GT Synth Pro Energy 5W30

<b>Description</b>	<p>A synthetic universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which special additives are added to obtain the following properties:</p> <ul style="list-style-type: none"><li>- a fast cold start</li><li>- a safe lubrication film at high temperatures</li><li>- a very good detergency and dispersion</li><li>- a very strong protection against wear, corrosion and foaming</li></ul>																		
<b>Application</b>	<p>This synthetic universal "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its low SAPS content this product can be applied in vehicles with modern three way catalyts and diesel particle filters.</p>																		
<b>Specifications</b>	<p>Performance level ACEA C2, C3 API SN BMW Longlife-04 GM dexos 2 MB 229.51/229.52 Porsche C30 VW 505.01</p>																		
<b>Typicals</b>	<table><tr><td>Density at 15 °C, kg/l</td><td>0,850</td></tr><tr><td>Viscosity -30 °C, mPa.s</td><td>6400</td></tr><tr><td>Viscosity 40 °C, mm<sup>2</sup>/s</td><td>74,40</td></tr><tr><td>Viscosity 100 °C, mm<sup>2</sup>/s</td><td>12,30</td></tr><tr><td>Viscosity Index</td><td>163</td></tr><tr><td>Flash Point COC, °C</td><td>242</td></tr><tr><td>Pour Point, °C</td><td>-36</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>7,8</td></tr><tr><td>Sulphate Ash, %</td><td>0,77</td></tr></table>	Density at 15 °C, kg/l	0,850	Viscosity -30 °C, mPa.s	6400	Viscosity 40 °C, mm <sup>2</sup> /s	74,40	Viscosity 100 °C, mm <sup>2</sup> /s	12,30	Viscosity Index	163	Flash Point COC, °C	242	Pour Point, °C	-36	Total Base Number, mgKOH/g	7,8	Sulphate Ash, %	0,77
Density at 15 °C, kg/l	0,850																		
Viscosity -30 °C, mPa.s	6400																		
Viscosity 40 °C, mm <sup>2</sup> /s	74,40																		
Viscosity 100 °C, mm <sup>2</sup> /s	12,30																		
Viscosity Index	163																		
Flash Point COC, °C	242																		
Pour Point, °C	-36																		
Total Base Number, mgKOH/g	7,8																		
Sulphate Ash, %	0,77																		