

GT Synth Pro Energy 5W30

Description

A fuel economy, synthetic, universal motor oil, developed according to the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- mid SAPS content
- suitable for modern catalysts
- a fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

Specifications

Performance level:
ACEA C3
API SN
BMW Longlife-04
MB 229.31/229.51
Porsche C30
VW 504.00/507.00

Typicals

Density at 15 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	5950
Viscosity 40 °C, mm ² /s	71,60
Viscosity 100 °C, mm ² /s	12,20
Viscosity Index	168
Flash Point COC, °C	234
Pour Point, °C	-39
Total Base Number, mgKOH/g	8,3
Sulphate Ash, %	0,74