

GT Synth Pro X Energy 10W40

Description	<p>This universal motor oil is based on high quality solvent refined mineral and synthetic base oils (reinforced with PAO and Ester). Additives have been added to this to obtain the following properties:</p> <ul style="list-style-type: none">- a stable viscosity index- a fast cold start- a strong resistance against oxidation- a safe lubrication film at high temperature- a good detergency and dispersion- a strong protection against wear, corrosion and foaming.																		
Application	<p>A universal motor oil, recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.</p>																		
Specifications	<p>Performance level: ACEA A3/B4 API SN/CF BMW Longlife-98 MB 229.1 VW 501.01/505.00</p>																		
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,870</td></tr><tr><td>Viscosity -25 °C, mPa.s</td><td>4900</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>87,10</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>13,30</td></tr><tr><td>Viscosity Index</td><td>154</td></tr><tr><td>Flash Point COC, °C</td><td>234</td></tr><tr><td>Pour Point, °C</td><td>-42</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>10,1</td></tr><tr><td>Sulphate Ash, %</td><td>1,29</td></tr></table>	Density at 15 °C, kg/l	0,870	Viscosity -25 °C, mPa.s	4900	Viscosity 40 °C, mm ² /s	87,10	Viscosity 100 °C, mm ² /s	13,30	Viscosity Index	154	Flash Point COC, °C	234	Pour Point, °C	-42	Total Base Number, mgKOH/g	10,1	Sulphate Ash, %	1,29
Density at 15 °C, kg/l	0,870																		
Viscosity -25 °C, mPa.s	4900																		
Viscosity 40 °C, mm ² /s	87,10																		
Viscosity 100 °C, mm ² /s	13,30																		
Viscosity Index	154																		
Flash Point COC, °C	234																		
Pour Point, °C	-42																		
Total Base Number, mgKOH/g	10,1																		
Sulphate Ash, %	1,29																		